



PRESSURE ADJUSTMENT FROM
700 TO 3,000 PSI DEPENDING
ON FLOW

FLOW CAPACITY: 20 GPM MAX.

PRESSURE SETTING: 2,000 ± 50 PSI
AT 10 GPM USING 164 SSU OIL AT
90 - 110° F

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED

Letters after dimensions defines
tolerances as follows:

A +/- 0.00015 G +/- 0.010
B +/- 0.0003 H +/- 0.020
C +/- 0.0005 J +/- 0.030
D +/- 0.001 K +/- 0.060
E +/- 0.002 L +/- 0.125
F +/- 0.005 Angle +/- 2°

THIS DRAWING AND ALL INFORMATION CONTAINED
ON IT IS THE PROPERTY OF ENERGY MFG. CO.,
INC. AND IS LOANED CONFIDENTIALLY AND MUST
NOT BE USED OR DISCLOSED DIRECTLY OR
INDIRECTLY IN ANY WAY DETRIMENTAL TO OUR
INTERESTS.

Material:

HT. Treat:
Finish:

Drawn by:

SA 03.14.73

Checked by:

C	REDRAWN IN CAD	07.20.04	ECN384
No.	Revision	Date	Appr. By

ENERGY MFG. CO., INC.

Title: RELIEF VALVE - 1/2 NPTF

Scale: FULL

A-4060